

Serial No.: 10/092,690

Attorney Docket No.: 02P03755US

IN THE CLAIMS:

This listing of the claims will replace all prior versions and listings of the claims in the application:

1. (Original) A telecommunications device, comprising:

an open loop power controller adapted to maintain a first phasing table and a channel-temperature table;

a closed loop power controller adapted to maintain a second phasing table and receive a power detector output;

wherein said open loop power controller is adapted to provide a power set (APC) value in a first mode and said closed loop power controller is adapted to provide said power set value in a second mode, and in said second mode, said closed loop power controller receives said power detector output during a transmit burst and after a transmit burst.

2. (Currently Amended) A telecommunications device ~~in accordance with claim 4, comprising:~~

an open loop power controller adapted to maintain a first phasing table and a channel-temperature table;

a closed loop power controller adapted to maintain a second phasing table and receive a power detector output;

wherein said open loop power controller is adapted to provide a power set (APC) value in a first mode and said closed loop power controller is adapted to provide said power set value in a second mode, and in said second mode, said closed loop power controller receives said power detector output during a transmit burst and after a transmit burst;

said first phasing table comprising pre-initialized power level and power set values.

Serial No.: 10/092,690

Attorney Docket No.: 02P03755US

3. (Original) A telecommunications device in accordance with claim 2, said second phasing table comprising pre-initialized power detector and power level values.
4. (Original) A telecommunications device in accordance with claim 2, said channel temperature table comprising a two-dimensional table of power set values with temperature and channel.
5. (Allowed) A telecommunications method for controlling transmit power in a wireless telecommunications device, comprising:
 - initializing first and second phasing tables, the first phasing table comprising pre-initialized power level and power set values, said second phasing table comprising pre-initialized power detector and power level values;
 - initializing a channel-temperature table, said channel temperature table comprising a two-dimensional table of power set values with temperature and channel;
 - generating a power set value using said first phasing table and said channel-temperature table in an open loop mode; and
 - generating a power set value by reading a power detector and accessing said second phasing table in a closed loop mode, wherein in said second mode said power detector is read while a transmitter is on and while a transmitter is off.
6. (Allowed) A method in accordance with claim 5, said initializing a first phasing table comprising adjusting the APC value until the nominal power for each power level is output from the telecommunications device and storing that value is stored in the first phasing table.
7. (Allowed) A method in accordance with claim 6, wherein said initializing said channel-temperature table comprising setting a number of telecommunications

Serial No.: 10/092,690

Attorney Docket No.: 02P03755US

devices to a specific channel and temperature;

adjusting the APC values of the telecommunications devices until the telecommunications devices output the nominal power for power level zero; and
averaging the results for each telecommunications device.

8. (Allowed) A method in accordance with claim 5, said generating a power set value in an open loop mode comprising determining a nominal APC value for the channel used to phase the telecommunications device by finding the closest higher channel and closest lower channel in the table, and interpolating between the room temperature APC values in the table.

9. (Allowed) A method in accordance with claim 5, said initializing said second phasing table comprising adjusting the APC value until the nominal power for each power level is output from the telecommunications device and storing the output of the power detector in the table.

10. (Allowed) A method in accordance with claim 9, said generating a power set value in a closed loop mode comprising:

reading the power detector to get an actual RF power value;
looking up the desired RF power value in the second phasing table;
obtaining an RF error; and
running a servo control loop calculation to find the APC value needed to correct for the RF error.

11. (Currently Amended) A telecommunications method, comprising:
providing an open loop power controller adapted to maintain a first phasing table and a channel-temperature table;

Serial No.: 10/092,690

Attorney Docket No.: 02P03755US

providing a closed loop power controller adapted to maintain a second phasing table and receive a power detector output;

wherein said open loop power controller is adapted to provide a power set (APC) value in a first mode and said closed loop power controller is adapted to provide said power set value in a second mode, said closed loop power controller receives said power detector output during a transmit burst and receives a power detector output after a transmit burst and uses the difference between the outputs to derive said APC value.

12. (Currently Amended) A telecommunications method in accordance with ~~claim 11, comprising:~~

providing an open loop power controller adapted to maintain a first phasing table and a channel-temperature table;

providing a closed loop power controller adapted to maintain a second phasing table and receive a power detector output;

wherein said open loop power controller is adapted to provide a power set (APC) value in a first mode and said closed loop power controller is adapted to provide said power set value in a second mode, said closed loop power controller receives said power detector output during a transmit burst and after a transmit burst;

said first phasing table comprising pre-initialized power level and power set values.

13. (Original) A telecommunications method in accordance with claim 12, said second phasing table comprising pre-initialized power detector and power level values.

14. (Original) A telecommunications method in accordance with claim 12, said channel temperature table comprising a two-dimensional table of power set values with temperature and channel

Serial No.: 10/092,690

Attorney Docket No.: 02P03755US

15. (Currently Amended) A telecommunications device, comprising:
- an open loop power controller adapted to provide a automatic power control (APC) value in a low power mode;
 - a closed loop power controller adapted to provide an APC value in a high power mode;
- wherein in said high power mode, said closed loop power controller receives a power detector output during a transmit burst and receives a power detector output after a transmit burst and uses the difference between the outputs to derive said APC value.